



## V-BELAY STATION 316L

**Ref: V50412**

Belay Station Type V in 316L stainless steel for outdoor environment / ecotri zinc plated for indoor environment. Two fixing points consisting of two Fixe 1 hangers M10 / M12 screws.

Anchor point with ring.

Designed and manufactured in Barcelona-Pyrenees.

### COMPONENT FEATURES

Hanger Fixe 1 - Geometry:

Rounded inner edge for less wear on the carabiners.

Directs the carabiner for an optimal roof work.

Conical Washer. Better control of the tightening torque.

Three anti-rotation pins.

Optimized surface for full contact.

Fixe 1-Hanger features:

For bolts M10 / M12.

Weight: 57g (10mm) / 56g (12mm).

Breaking strength: 25 kN.

Material: ecotri zinc plated / 316L stainless steel.

Ring features:

Ring always present between components for a better workability.

TIG welding. Better resistance to corrosion.

Inside diameter 33mm.

Breaking strength: 25 kN.

Material: ecotri zinc plated / 316L stainless steel.

Features of the 316L stainless steel-chain:

TIG welding. Better resistance to corrosion.

Reduction of the number of links to three. Less critical points.



7mm link-rod diameter.

Useful length: 185mm.

Breaking strength: 25kN.

Material: 316L stainless steel.

Features of the ecotri zinc plated-chain:

7mm link-rod diameter.

Useful length: 185mm.

Breaking strength: 25kN.

Material: ecotri zinc plated steel.

Información técnica:

Brand:	Fixe
Diameter:	12mm
Country of origin:	Spain
Color:	Inox
Material:	316L
Breaking Strenght:	25kN
Configurator:	Si
Fusion:	No
8m mark:	No
Reflector:	No
Ultrasonic finish:	No