



V-BELAY STATION ECOTRI

Ref: V50212

Type V meeting in 316L stainless steel for outdoor environments / ecotri zinc-plated for indoor environments. Two fixing points composed of two Fixe 1 plates for M10 / M12 screws. Anchorage point with ring. Designed and manufactured in Barcelona-Pirineus. CHARACTERISTICS OF THE COMPONENTS Fixe 1 plate geometry:- Rounded inner edge for less carabiner wear.- Directs the carabiner for optimum work on roofs.- Conical Washer. More torque control.- Three anti-rotation pins.- Optimised surface for full contact. Features Fixe 1 plate:- For M10/M12 screws.- Weight: 57g (M10)/56 (M12).- Ultimate strength: 25kN.- Material: ecotri zinc plated steel / 316L stainless steel. Features of the ring:- Always present ring between components for better manoeuvrability.- TIG welding. Better corrosion resistance.- Inner diameter: 33mm.- Limit resistance: 25kN.- Material: ecotri zinc plated steel / 316L stainless steel. Characteristics of 316L stainless steel chain:- TIG welding. Better corrosion resistance.- Reduction of the number of links to three. Fewer critical points.- Link rod diameter: 7mm.- Useful length: 185mm.- Ultimate strength: 25kN.- Material: 316L stainless steel. Features of ecotri zinc plated steel chain:- Link rod diameter: 7mm.- Working length: 185mm.- Ultimate strength: 25kN.- Material: ecotri zinc plated steel.

Belay Station Type V in 316L stainless steel for outdoor environment / ecotri zinc plated for indoor environment. Two fixing points consisting of two Fixe 1 hangers M10 / M12 screws. Anchor point with ring. Designed and manufactured in Barcelona-Pyrenees.

COMPONENT FEATURES
Hanger Fixe 1 - Geometry:

Rounded inner edge for less wear on the carabiners.

Directs the carabiner for an optimal roof work.

Conical Washer. Better control of the tightening torque.

Three anti-rotation pins.

Optimized surface for full contact.

Fixe 1-Hanger features:

For bolts M10 / M12.

Weight: 57g (10mm) / 56g (12mm).

Breaking strength: 25 kN.

Material: ecotri zinc plated / 316L stainless steel.

Ring features:



Ring always present between components for a better workability.

TIG welding. Better resistance to corrosion.

Inside diameter 33mm.

Breaking strength: 25 kN.

Material: ecotri zinc plated / 316L stainless steel.

Features of the 316L stainless steel-chain:

TIG welding. Better resistance to corrosion.

Reduction of the number of links to three. Less critical points.

7mm link-rod diameter.

Useful length: 185mm.

Breaking strength: 25kN.

Material: 316L stainless steel.

Features of the ecotri zinc plated-chain:

7mm link-rod diameter.

Useful length: 185mm.

Breaking strength: 25kN.

Material: ecotri zinc plated steel.

Información técnica:

Brand:	Fixe
Diameter:	12mm
Country of origin:	Spain
Color:	Ecotri
Material:	Steel



Breaking Strenght:	25kN
Configurator:	Si
Fusion:	No
8m mark:	No
Reflector:	No
Ultrasonic finish:	No